

PCT

REQUEST

For receiving Office use only	
International Application No.	
International Filing Date	
Name of receiving Office and "PCT International Application"	

The undersigned requests that the present international application be processed according to the Patent Cooperation Treaty.	Name of receiving Office and "PCT International Application"			
	Applicant's or agent's ti (if desired) (12 characters n	A 700 04 /5100 1		
Box No. 1 TITLE OF INVENTION				
ABSOLUTE HUMIDITY SENSOR				
Box No. II APPLICANT				
Name and address: (Family name followed by given name: for a designation. The address must include postal code and name of cou address indicated in this Box is the applicant's State (that is, country of residence is indicated below.)		This person is also inventor.		
LG ELECTRONICS INC.		Telephone No. (82) (02) 3777-7093		
20, Yoido-dong, Youngdungpo-gu,		Facsimile No. (82) (02) 3777-5151		
Seoul, 150-010, Republic of Korea		Teleprinter No.		
State (that is, country) of nationality:	State (that is, country) o	f residence: KR		
This person is applicant for the purposes of: all designated		the States indicated in the Supplemental Box		
Box No. III FURTHER APPLICANT(S) AND/OR (FURT	HER) INVENTOR(S)			
Name and address: (Family name followed by given name; for a designation. The address must include postal code and name of counaddress indicated in this Box is the applicant's State (that is, country, of residence is indicated below.)		This person is:		
LEE, Don Hee		X applicant and inventor		
Samik APT., 1-1109, 572, Pisan-dong,				
Tongan-gu, Anyang-shi, Kyonggi-do,		inventor only (If this check-bax is marked, do not fill in below.)		
431-050, Republic of Korea				
State (that is, country) of nationality:	State (that is, country) of	residence: KR		
This person is applicant all designated for the purposes of:		e United States America only the States indicated in the Supplemental Box		
X Further applicants and/or (further) inventors are indicated or	n a continuation sheet.			
Box No. IV AGENT OR COMMON REPRESENTATIVE;	OR ADDRESS FOR C	ORRESPONDENCE		
The person identified below is hereby/has been appointed to act or of the applicant(s) before the competent International Authorities a	n behalf	gent common representative		
Name and address: (Family name followed by given name; for a designation. The address must include postal code		Telephone No. (82) (02) 3453-6701		
KIM, Yong In, KANG, Yong Bok		Facsimile No.		
15th Floor, Yo Sam Bldg., 648-23	(82) (02) 557-3404			
Yeoksam-dong, Kangnam-ku,		Teleprinter No.		
Seoul, 135-080, Republic of Korea				
Address for correspondence: Mark this check-box where no	agent or common representation	entative is/has been appointed and the ld be sent.		


			_
Sheet	Nο		4

Continuation of Box No. 111 FURTHER APPLICANT(S) AND/OR (FURTHER) INVENTOR(S)						
If none of the following sub-boxes is used, this sheet should not be included in the request.						
Name and address: (Family name followed by given name: for a lastignation. The address must include postal code and name of cour address indicated in this Box is the applicant's State (that is, country) of residence is indicated below.) BU, Jong Uk Hanjin APT., 701-1303, Chongja-dong, Pundang-gu, Songnam-shi, Kyonggi-do, 463-010, Republic of Korea						
State (that is, country) of nationality:	State (that is, country) of residence:					
This person is applicant all designated for the purposes of:	States except tes of America only the States indicated in the Supplemental Box					
Name and address: (Family name followed by given name: for a le designation. The address must include postal code and name of coun address indicated in this Box is the applicant's State (that is, country) of residence is indicated below.)	This person is: applicant only applicant and inventor inventor only (If this check-bax is marked, do not fill in below.)					
State (that is, country) of nationality:	State (that is, country) of residence:					
This person is applicant for the purposes of: all designated lall designated the United States	States except the United States the States indicated in the Supplemental Box					
Name and address: (Family name followed by given name: for a le designation. The address must include postal code and name of count address indicated in this Box is the applicant's State (that is, country) of residence is indicated below.)	gal entity, full official ry. The country of the of residence if no State This person is: applicant only applicant and inventor inventor only (If this check-box is marked, do not fill in below.)					
State (that is, country) of nationality:	State (that is, country) of residence:					
This person is applicant all designated for the purposes of:						
Name and address: (Family name followed by given name; for a les designation. The address must include postal code and name of count address indicated in this Box is the applicant's State (that is, country), of residence is indicated below.)	rv. The country of the 1					
State (that is, country) of nationality:	State (that is, country) of residence:					
	the United States 1 the States indicated in					
This person is applicant all designated of the purposes of: all designated of the United States the United States	es of America only the Supplemental Box					
Further applicants and/or (further) inventors are indicated on	another continuation sheet.					

Bd	x No	V DESIGNATION OF STATES							
		owing designations are hereby made under Rule 4.9(a) (a)	nark	the ap	plicable check-boxes; at least one must be marked):				
Re	giona	al Patent	٠.		. MANA Molowi, SD Sudan, SL Sierra Leone, SZ Swaziland				
		TZ United Republic of Tanzania, UG Ogaida, 2W 2mi	Out	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	o. MW Malawi, SD Sudan, SL Sierra Leone, SZ Swaziland dany other State which is a Contracting State of the Harare				
		Eurasian Patent: AM Armenia, AZ Azerbaijan, BY Belarus, KG Kyrgyzstan, KZ Kazakhstan, MD Republic of Moldova, RU Russian Federation, TJ Tajikistan, TM Turkmenistan, and any other State which is a Contracting State of the Eurasian Patent Convention and of the PCT Convention and of the PCT European Patent: AT Austria, BE Belgium, CH and LI Switzerland and Liechtenstein, CY Cyprus, DE Germany. European Patent: AT Austria, BE Belgium, CR Injury Kingdom, CR Greece, IE Ireland, IT Italy, LU Luxembourg.							
		MC Monaco, NL Netherlands, PT Portugal, SE Sweden,	and	anyo	ther State which is a Contracting State of the European Patent				
X	OA	OAPI Patent: BF Burkina Faso. BJ Benin, CF Centi GA Gabon, GN Guinea, GW Guinea-Bissau, ML Mali,	14117	a State	n Republic, CG Congo. Cl Côte d'Ivoire, CM Cameroon, itania. NE Niger, SN Senegal, TD Chad, TG Togo, and any e of the PCT (if other kind of protection or treatment desired.				
		specify on aonea line)	aifir.	n dott	ad line)				
		al Patent (if other kind of protection or treatment desired, spe							
X	ΑE	United Arab Emirates	X	LR	Liberia				
\mathbf{X}	AL	Albania	X	LS	Lesotho				
ſΧΙ	AM	Armenia	X	LT	Lithuania –				
X	AT	Austria	X	LU	Luxembourg				
121	AH	Australia	X	LV	Latvia				
		Azerbaijan	X	MA	Morocco				
			121	MD	Republic of Moldova				
		Bosnia and Herzegovina			Madagascar				
IXI	BB	Barbados		WIG	Wadagascar				
X	BG	Bulgaria	IX.	MK	The former Yugoslav Republic of Macedonia				
X	BR	Brazil							
X	BY	Belarus	X	MN	Mongolia				
		Canada	\boxtimes	MW	Malawi				
		and LI Switzerland and Liechtenstein	X	MX	Mexico				
		China	X	NO	Norway				
	C.Y	Costa Rica	=	NZ	New Zealand				
X	CK	Cuba	=	PL	Poland				
			=	PT	Portugal				
X	CZ	Czech Republic		_					
IXI	ĐE	Germany	=	RO	Romania Russian Federation				
		Denmark		RU					
X	DM	Dominica		SD	Sudan				
\mathbf{X}	EE	Estonia		SE	Sweden				
X	ES	Spain		SC	Singapore				
X	FI	Finland	=	SI	Slovenia				
X	GB	United Kingdom	Z	SK	Slovakia				
X	GD	Grenada	X	SL	Sierra Leone				
X	GΕ	Georgia	X	TJ	Tajikistan				
M	GH	Ghana	\boxtimes	TM	Turkmenistan				
X	GM	Gambia	X	TR	Turkey				
X	HR	Croatia	\square	TT	Trinidad and Tobago				
_	HU	Hungary	X	TZ	United Republic of Tanzania				
X		Indonesia	X	UA	Ukraine				
X		Israel	[X]	UG	Uganda				
X		India	_	US	United States of America				
X		Iceland	Ø	UZ	Uzbekistan				
لكا	JP	Japan	=	VN	Viet Nam				
X	KE	Kenya	=		Yugoslavia				
\mathbf{X}	KG	Kyrgyzstan	=	YU	South Africa				
\boxtimes	ΚP	Democratic People's Republic of Korea	_	ZA	Zimbabwe				
П	KR	Republic of Korea	Ch	ZW eck-t	loves reserved for designating States which have				
Ā	V7	Kazakhstan	bec	ome	party to the PC t after issuance of this sheet.				
		G : Ll							
Pre- desi tron	Precautionary Designation Statement: In addition to the designations made above, the applicant also makes under Rule 4.9(b) all other designations which would be permitted under the PCT except any designation(s) indicated in the Supplemental Box as being excluded designations which would be permitted under the PCT except any designation(s) indicated in the Supplemental Box as being excluded designations which would be permitted under the PCT except any designation are subject to confirmation and that any trom the scope of this statement. The applicant declares that those additional designations are subject to confirmed before the expiration of 15 months from the priority date is to be regarded as withdrawn by the applicant designation which is not confirmed before the expiration of 15 months from the priority (life for within the 15-month time limit.)								
at th	e exp	on which is not confirmed before the expiration of 15 months piration of that time limit. (Confirmation (including fees) mus	t rea	ch the	receiving Office within the 13-month time time.				

Sheet No. ...4...

Box No. VI PRIORITY CLAIM				Further priority claims are indicated in the Supplemental Box				
Filing date Number			Where earlier application is:					
of earlier application (day/month/year)	of earl	ier applicatio	on	national applic country	1	regional application:* regional Office	international application receiving Office	
item (1) 13, December 1999 (13, 12,1999)	199	9-57196		KR				
item (2)								
item (3)			-					
The receiving Office is req of the earlier application(s purposes of the present int	s) (only if Pernationa	the eartier a Lapplication	is the	ation was jiteu w e receiving Office,) identifi	ed above as item(s):		
Where the earlier application is a Convention for the Protection of In	an ARIPO e dustrial Pr	application, it operty for whic	ıs mai ch tha	ndatory to indicate it earlier application	in the Sup n was filed	pplemental Box at least on (Rule 4.10(b)(ii)). See Su	e country party to the Paris pplemental Box.	
Box No. VII INTERNATIO	NAL SE	ARCHING	AUT	HORITY			-	
Choice of International Search (if two or more International Sea competent to carry out the interna- the Authority chosen; the two-letter	arching Aus ational seas	rch indicate	searc	uest to use result th has been carried to the (day/month/year)	its of ear	requested from the internati	to that search (if an earlie ional Searching Authority): Country (or regional Office,	
ISA/ AT								
Box No. VIII CHECK LIST	; LANG	UAGE OF F	TILIN	vG				
This international application co	ontains	This interna	tiona	l application is ac	compani	ied by the item(s) marke	ed below:	
	4	1. 😧 fee ca						
description (excluding	+			igned power of att		rafarance number if any	<i>γ</i> .	
sequence listing part) : 1	-					reference number, if any	'•	
Clainto	2			explaining lack of		ox No. VI as item(s): (1	١	
aosa act	1					on into (language):	,	
T	5	o. [] traits	nauon	dications concert	nina dena	sited microorganism or	other biological material	
sequence listing part of description :						ce listing in computer re		
	3	9. dother			,			
Total number of sheets: 2 Figure of the drawings which should accompany the abstract:	2		Lan	iguage of filing o	of the	English		
Par No IV SIGNATURE	OF APPL	ICANT OR	AGE	ENT				
Next to each signature, indicate the nan	ne of the per	son signing and	the ca	apacity in which the pe	erson signs	(if such capacity is not obvio	us from reading the request).	
KIM, Yo				(Seal)				
KANG, Y	ong E	Bok		(Seal)				
			or rec	ceiving Office use	e only —		2. Drawings:	
 Date of actual receipt of the international application: 							<u> </u>	
 Corrected date of actual rece timely received papers or dra the purported international a 	awings co	mpieting					received:	
Date of timely receipt of the corrections under PCT Artic	requir e d le [1(2):						not received:	
 International Searching Auth (if two or more are competen 	ority ISA			l l un	nil search	of search copy delayed fee is paid.		
		For l	Intern	ational Bureau us	se only =			
Date of receipt of the record cop	ру							



PCT

INTERNATIONAL SEARCH REPORT

(PCT Article 18 and Rules 43 and 44)

Applicant's or agent's file reference AZ00-0175WO			FOR FURTHER see Notification of Transmittal of International Search Report ACTION (Form PCT/ISA/220) as well as, where applicable, item 5 below.						
Inter	mational app	lication No.	International filing da	ite (day/month/year)	(Earliest) Priority Date (day/month/year)				
1	T/KR 00			2000 (12.12.2000)	13 December 1999 (13.12.1999)				
Арр	licant								
LG	ELECT	RONICS INC.							
L				Combing Autho	sity and is transmitted to the applicant				
Thi	s internation ording to A	nal search report has bee rticle 18. A copy is bein	n prepared by this light transmitted to the	International Bureau.	rity and is transmitted to the applicant				
Thi	s internation	nal search report consist	s of a total of3	sheets.					
		It is also accompani	ed by a copy of each	prior art document cited in t	his report.				
1.	lang	regard to the language, uage in which it was file	d, unless otherwise	indicated under this item.	sis of the international application in the				
		Authority (Rule 23.1(b)).		international application furnished to this				
	h With	regard to any nucleotid th was carried out on the	e and/or amino aci	d sequence disclosed in the ice listing:	nternational application, the international				
		contained in the internat	ional application in	written form.					
		filed together with the ir	nternational applicati	ion in computer readable for	n.				
		furnished subsequently (
		furnished subsequently to this Authority in computer readable form.							
	intern	the statement that the su national application as fil	bsequently furnished led has been furnished	d written sequence listing doe ed.	es not go beyond the disclosure in the				
					identical to the written sequence listing has				
2.		Certain claims were fo	und unsearchable (See Box I)					
3.	_	Unity of invention is la							
4.	_	ard to the title.							
		the text is approved as s	ubmitted by the app	licant.					
		the text has been established							
5.	With rega	ard to the abstract.							
		the text is approved as s	ubmitted by the app	licant.					
		-L has have astable	shed according to R	ule 38.2(b), by this Authority	y as it appears in Box III. The applicant may, port, submit comments to this Authority.				
6.			-	bstract is Figure No.: 2A					
J.,		as suggested by the appl			None of the figures.				
		because the applicant fa		ıre.					
	-	because this figure bette							
		because this figure bette	r characterizes the i	nvention.					

CLASSIFICATION OF SUBJECT MATTER IPC⁷: G01N 27/12 According to International Patent Classification (IPC) or to both national classification and IPC FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) IPC⁷: G01N 27/12, G01N 27/22, G01N 27/18 Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) WPI C. DOCUMENTS CONSIDERED TO BE RELEVANT Citation of document, with indication, where appropriate, of the relevant passages Relevant to claim No. 1-3,5-7 X GB 2194845 A (SHARP) 16 March 1988 (16.03.88) the whole document. Υ 4,8,9 Υ WO 91/03734 A1 (AT & S) 21 March 1991 (21.03.91) 4 abstract. Υ EP 021225 A1 (SHIBAURA DENSHI) 7 January 1981 (07.01.81) 8,9 See patent family annex. Further documents are listed in the continuation of Box C. "T" later document published after the international filing date or priority Special categories of cited documents: ...A" document defining the general state of the art which is not date and not in conflict with the application but cited to understand considered to be of particular relevance the principle or theory underlying the invention ..E" earlier application or patent but published on or after the international "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step filing date ..L" document which may throw doubts on priority claim(s) or which is when the document is taken alone cited to establish the publication date of another citation or other "Y" document of particular relevance; the claimed invention cannot be special reason (as specified) considered to involve an inventive step when the document is "O" document referring to an oral disclosure, use, exhibition or other combined with one or more other such documents, such combination being obvious to a person skilled in the art ..P" document published prior to the international filing date but later than "&" document member of the same patent family the priority date claimed Date of the actual completion of the international search Date of mailing of the international search report 30 March 2001 (30.03.2001) :6 March 2001 (16.03.2001) Name and mailing adress of the ISA/AT Authorized officer Austrian Patent Office NARDAI Kohlmarkt 8-10; A-1014 Vienna

Telephone No. 1/53424/347

Facsimile No. 1/53424/535

INTERN NAL SEARCH REPORT Information on patent family members



International application No. PCT/KR 00/01440

Patent document cited in search report			Publication date		Patent memb		Publication date
EP	A	021225				none	
GB	Al	2194845	16-03-1988	DE	A1	3724966	04-02-1988
GB	B2	2194845	24-10-1990	DE	C2	3724966	26-10-1989
				DE	C3	3724966	21-03-1996
				GB	A0	8717919	03-09-1987
				US	Α	4928513	29-05-1990
				J₽	A2	63145954	18-06-1988
				J₽	A2	63263426	31-10-1988
				JР	В4	7095002	11-10-1995
				JР	A2	63289443	25-11-1988
				JP	A2	63293459	30-11-1988
WO.	Al	9103734	21-03-1991	DE	CO	59010077	29-02-1996
				EP	A1	489825	17-06-1992
				EP	Al	489826	17-06-1992
				EP	B1	489826	17-01-1996
				FI	A0	920916	28-02-1992
				FI	A0	920917	28-02-1992
				FI	B1	100618	15-01-1998
				JP	Т2	5505234	05-08-1993
				JP	T2	5506711	30-09-1993
				US	A	5348761	20-09-1994
				WO	Al	9103735	21-03-1991
				ΑT	A	571/90	15-07-1997
				ΑT	В	403527	25-03-1998

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 14 June 2001 (14.06.2001)

PCT

(10) International Publication Number WO 01/42775 A1

Uk [KR/KR]; Hanjin APT., 701-1303, Chongja-dong,

648-23, Yeoksam-dong, Kangnam-ku, Scoul 135-080

(51) International Patent Classification7:

G01N 27/12

Pundang-gu, Songnam-shi, Kyonggi-do 463-010 (KR).

(21) International Application Number: PCI/KR00/01440

(22) International Filing Date:

12 December 2000 (12.12.2000)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

1999/57196

13 December 1999 (13.12.1999)

(71) Applicant (for all designated States except US): LG ELECTRONICS INC. [KR/KR]; 20, Yoido-dong, Youngdungpo-gu, Seoul 150-010 (KR).

(72) Inventors; and

(75) Inventors/Applicants (for US only): LEE, Don, Hee [KR/KR]; Samik APT., 1-1109, 572, Pisan-dong, Tongan-gu, Anyang-shi, Kyonggi-do 431-050 (KR). BU, Jong, (74) Agents: KIM, Yong, In et al.: 15th Floor, Yo Sam Bldg.,

- (81) Designated States (national): AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU. CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN. IS. JP. KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA. ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, Fl, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).


Published:

(KR).

With international search report.

[Continued on next page]

(54) Title: ABSOLUTE HUMIDITY SENSOR



(57) Abstract: An absolute humidity sensor for a microwave oven is disclosed. The absolute humidity sensor includes a silicon substrate, a humidity sensing element formed on a substrate, for detecting humidity exposed to the air, having a variable resistance value depending on the amount of the humidity, a temperature compensating element formed on the semiconductor, for compensating for the resistance value of the humidity sensing element, and a passivation film covered on the temperature compensating element, for shielding the humidity exposed to the air so as not to vary the resistance value of the temperature compensating element. The humidity sensing element and the temperature compensating element include an insulating film formed on the substrate, a humidity sensing film formed on the insulating film, for absorbing the humidity, and an electrode formed below the humidity sensing film or over/below the humidity sensing film. A polyimide thin film, which absorbs the humidity greater than a ceramic based humidity sensing material, is used as a humidity sensing material, and a silicon wafer is used as a substrate. Thus, an absolute humidity sensor susceptible to humidity can be fabricated and at the same time the sensor is integrated using a silicon process to facilitate its mass production.





For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

JC03 Rec'd PCT/PTO 1 3 AUG 2001

ABSOLUTE HUMIDITY SENSOR

Technical Field

The present invention relates to an absolute humidity sensor, and more particularly, to an absolute humidity sensor for a microwave oven.

Background Art

10

15

20

25

Generally, a humidity sensor is used for various purposes, for example, in a hygrometer, a humidity sensor for cooking of food in a microwave oven, and the like. Examples of currently used humidity sensors include a capacitance type humidity sensor, a relative humidity sensor, and an absolute humidity sensor. The capacitance type humidity sensor is based on variation of dielectric constants by hygroscopic property of an organic material such as polyimide. The relative humidity sensor is based on resistance variation of a semiconductor ceramic such as MgCr₂O₄. The absolute humidity sensor is based on a ceramic thermistor.

Of the humidity sensors, the absolute humidity sensor based on two thermistors is widely used as a humidity sensor for cooking of food in a microwave oven.

The absolute humidity sensor has an advantage in that it can stably detect the humidity because it is not susceptible to variation of a peripheral temperature.

The principles of sensing humidity of the absolute humidity sensor in the microwave oven are based on resistance variation by temperature variation of a thermistor as vapor generated from food during cooking of

food absorbs heat of the thermistor.

10

15

20

25

Fig. 1 shows a structure of a background art absolute humidity sensor. Referring to Fig. 1, two ceramic thermistors 1 and 2 coated with a passivation film such as a glass film are floating by being connected to a support pin 4 by a precious metal conductor 3 such as platinum. The ceramic thermistors 1 and 2 are packaged by a metal shield case 5 that isolates the two thermistors 1 and 2 from each other.

The thermistor 1 is exposed to the air to allow vapor to be in contact with a surface of the thermistor 1 by means of a fine hole of the metal shield case 5. The thermistor 1 is used as a sensing element. The other thermistor 2 is sealed in a dry N_2 by the metal shield case 5 so as not to be in contact with the vapor. The thermistor 2 is used as a reference element.

Therefore, if a bridge circuit consists of the two thermistors 1 and 2 and an external resistor, the vapor generated from food during cooking of food absorbs heat of the thermistor 1 exposed to the air. Thus, resistance variation occurs in only the exposed thermistor 1. In this case, output variation occurs due to a bias voltage, thereby detecting the humidity.

Since the background art humidity sensor uses an element as a ceramic thermistor, heat capacity is great and thus sensitivity is low.

Also, response time is slow and the size of the sensor becomes greater.

Furthermore, the thermistor element is floating using the conductor 3 and the support pin 4 as shown in Fig. 1, and the conductor 3 and the pin 4 are spot-welded. For assembly, the reference element 2 should be sealed in a dry N_2 . For this reason, the fabrication process

steps are complicate and the number of the process steps increases. Also, the cost is expensive and mass production is disadvantageous.

Disclosure of the Invention

5

10

20

25

Accordingly, the present invention is directed to an absolute humidity sensor that substantially obviates one or more of the problems due to limitations and disadvantages of the background art.

An object of the present invention is to provide an absolute humidity sensor having excellent humidity hygroscopic property.

Another object of the present invention is to provide an absolute humidity sensor having simple process steps to facilitate mass production.

Additional features and advantages of the invention will be set forth in the description which follows, and in part will be apparent from the description, or may be learned by practice of the invention. The objectives and other advantages of the invention will be realized and attained by the structure particularly pointed out in the written description and claims hereof as well as the appended drawings.

To achieve these and other advantages and in accordance with the purpose of the present invention, as embodied and broadly described, an absolute humidity sensor according to the present invention includes a silicon substrate, a humidity sensing element formed on a substrate, for detecting humidity exposed to the air, having a variable resistance value depending on the amount of the humidity, a temperature compensating element formed on the semiconductor, for compensating for the resistance value of the humidity sensing element, and a passivation film covered on

the temperature compensating element, for shielding the humidity exposed to the air so as not to vary the resistance value of the temperature compensating element.

In the preferred embodiment of the present invention, the humidity sensing element and the temperature compensating element include an insulating film formed on the substrate, a humidity sensing film formed on the insulating film, for absorbing the humidity, and an electrode formed below the humidity sensing film or over/below the humidity sensing film.

The insulating film and the passivation film are formed of any one of SiO_2 , Si_3N_4 , and SiO_xN_y . The humidity sensing film is formed of polyimide annealed at a temperature of $200{\sim}300\,{\circ}$. The electrode uses a comb electrode.

10

15

20

The absolute humidity sensor according to the present invention further includes a printed circuit board joined with a lower portion of the silicon substrate, a wire which electrically connects electrodes of the humidity sensing element and the temperature compensating element with electrodes of the printed circuit board, and a metal shield case formed over the printed circuit board to cover an entire surface of the printed circuit board including the humidity sensing element and the temperature compensating element.

In the preferred embodiment of the present invention, a polyimide thin film, which absorbs the humidity greater than a ceramic based humidity sensing material, is used as a humidity sensing material, and a silicon wafer is used as a substrate. Thus, an absolute humidity sensor susceptible to humidity can be fabricated and at the same time the sensor

is integrated using a silicon process to facilitate its mass production.

It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

5

10

20

25

Brief Description of the Drawings

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and together with the description serve to explain the principles of the invention.

In the drawings:

Fig. 1 is a structural sectional view showing a background art of an absolute humidity sensor;

15 Figs. 2a and 2b are structural perspective views showing a resistance type absolute humidity sensor according to the present invention;

Figs. 3a and 3b are structural perspective views showing a capacitance type absolute humidity sensor according to the present invention;

Figs. 4a and 4b show a structure of an absolute humidity sensor package according to the present invention; and

Fig. 5 is a circuit diagram for detecting the humidity based on the resistance type absolute humidity sensor according to the present invention.

5

Best Mode for Carrying Out the Invention

Reference will now be made in detail to the preferred embodiments of the present invention, examples of which are illustrated in the accompanying drawings.

First Embodiment

5

10

15

20

25

Figs. 2a and 2b are structural perspective views showing a resistance type absolute humidity sensor according to the present invention.

As shown in Fig. 2a, an insulating film 7 of SiO_2 , Si_3N_4 , or SiO_xN_y is formed on a silicon substrate 6. A metal film such as Al or Pt is deposited on the insulating film 7 and then patterned to form a pair of electrodes 8 and 8' in a comb shape.

Afterwards, a polyimide thin film is spin-coated on the electrode and then patterned to form a humidity sensing film 9 for a humidity sensing element and a humidity sensing film 9' for a temperature compensating element.

The polyimide is imidized at a temperature of about 200°C or greater. The polyimide has a thermal decomposition temperature of about $450\sim500$ °C. Accordingly, the polyimide has excellent thermal stability.

Also, the polyimide has a hygroscopic property as follows.

An equilibrium value of an aqueous molecule absorbed into the polyimide at a room temperature under the ambient of a relative humidity ambient of 80% is about 2.3wt%. The polyimide absorbs humidity more than a ceramic based humidity sensing material. Moreover, a diffusion coefficient of the aqueous molecule within a polyimide thin film is approximately 5 x 10^{-9} cm²/sec at a room temperature. Accordingly, high

response time can be obtained.

The polyimide thin film has a compact film tissue when annealing is performed at a high temperature of about $300\,^{\circ}\mathrm{C}$ or greater. In this case, it is difficult to propagate the humidity into the film. To use the polyimide thin film as a humidity sensing element, the annealing process is preferably performed at a temperature between $200\,^{\circ}\mathrm{C}$ and $300\,^{\circ}\mathrm{C}$ to obtain high hygroscopic ratio of the polyimide film.

After the humidity sensing films 9 and 9' are formed, a ceramic thin film such as SiO_2 , Si_3N_4 , and SiO_xN_y is deposited on the humidity sensing film 9' for a temperature compensating element and then patterned, so that the humidity is not propagated into the humidity sensing film 9'. Thus, a passivation film 10 is formed.

In the resistance type absolute humidity sensor fabricated as above, it is noted that, as shown in Fig. 2b, the humidity sensing element and the temperature compensating element are formed on the same silicon substrate 6.

Second Embodiment

10

15

20

25

Figs. 3a and 3b are structural perspective views showing a capacitance type absolute humidity sensor according to the present invention.

As shown in Fig. 3a, an insulating film 12 of SiO_2 , Si_3N_4 , or SiO_xN_y is formed on a silicon substrate 11. A metal film such as Al or Pt is deposited on the insulating film 12 and then patterned to form a lower electrode 13 for a humidity sensing element and a lower electrode 13' for a temperature compensating element.

Afterwards, a polyimide thin film is spin-coated on the lower

electrodes 13 and 13' and then patterned to form a humidity sensing film 14 for a humidity sensing element and a humidity sensing film 14' for a temperature compensating element. Subsequently, an annealing process is performed at a temperature between $200\,\mathrm{C}$ and $300\,\mathrm{C}$.

5

10

15

20

25

The metal film having the same material as that of the lower electrodes 13 and 13' is deposited on the polyimide humidity sensing films 14 and 14' and then patterned to form an upper electrode 15 for a humidity sensing element and an upper electrode 15' for a temperature compensating element in a comb shape. Thus, a parallel capacitor structure is formed in such a manner that the polyimide humidity sensing film is formed between the upper and lower electrodes.

Unlike the lower electrodes 13 and 13', the upper electrodes 15 and 15' are formed in a comb shape to allow an aqueous molecule to smoothly pass through the polyimide humidity sensing film, thereby partially exposing the polyimide thin film.

Accordingly, the vapor is directly in contact with the polyimide humidity sensing film exposed between the upper electrodes, so as to be propagated into the thin film.

The polyimide has a relative dielectric constant of 3 to 4 at a room temperature. Also, the polyimide has a dissipation factor value of 0.001~0.003 at the frequency of 1kHz. Accordingly, the polyimide has a stable dielectric property.

In the present invention, since the polyimide humidity sensing film acts as a dielectric of a capacitor, dielectric mixtures having different dielectric constants are formed within the polyimide thin film if the aqueous molecule having a relative dielectric constant of 80 is

propagated into the polyimide thin film.

5

10

15

20

Thus, the relative dielectric constant of the dielectric mixtures is varied depending on variation of the peripheral humidity, so that the humidity variation can be detected.

Finally, a ceramic thin film such as SiO_2 , Si_3N_4 , and SiO_xN_y is deposited on the humidity sensing film 14' for a temperature compensating element and the upper electrode 15' and then patterned, so that the humidity is not propagated into the humidity sensing film 14'. Thus, a passivation film 16 is formed.

In the capacitance type absolute humidity sensor fabricated as above, it is noted that, as shown in Fig. 3b, the humidity sensing element and the temperature compensating element are formed on the same silicon substrate 11.

Figs. 4a and 4b show a package structure of an absolute humidity sensor according to the present invention, in which one example of the resistance type absolute according to the first embodiment of the present invention is shown.

As shown in Fig. 4a, an absolute humidity sensor element 19 provided with a humidity sensing element 18 and a temperature compensating element 18 as fabricated by the method of the first embodiment is joined with a printed circuit board 20. Electrodes 8 and 8' of the elements are wire-bonded to an electrode 21 of the printed circuit board 20. Afterwards, as shown in Fig. 4b, a shield wire 22 is connected to the printed circuit board 20. The shield wire 22 and the printed circuit board 20 are sealed with a metal shield case 23 having a hole to propagate the humidity thereinto. Thus, the package of the absolute humidity sensor is

completed.

10

15

20

25

Fig. 5 is a circuit diagram for detecting variation of the peripheral humidity based on the resistance type absolute humidity sensor according to the present invention. The circuit for detecting variation of the peripheral humidity includes a bridge circuit and a power source V applied to the bridge circuit. The bridge circuit consists of a humidity sensing element 17, a temperature compensating element 18, a fixed resistor R1, and a variable resistor VR.

As an example, a method for detecting variation of the humidity by the water vapor generated from food during cooking of food in a microwave oven using the absolute humidity sensor and the above circuit will be described below.

First, if the food is heated in the microwave oven, the water vapor is generated. The generated water vapor is propagated into the metal shield case 23 through the hole formed therein. Thus, the water vapor is in contact with the humidity sensing element 17 and the temperature compensating element 18.

At this time, the humidity sensing element 17 has a varied resistance as the humidity is absorbed in the polyimide. However, the temperature compensating element 18 does not have a varied resistance as the humidity is not absorbed in the polyimide due to the passivation film.

The resistance variation of the humidity sensing element 17 causes output variation of the bridge circuit, thereby detecting the humidity variation.

Accordingly, the humidity variation around the sensor can easily be detected by the absolute humidity sensor and the above circuit. The water

vapor generated from the food due to heat during cooking of food in a cooking machine such as a microwave oven is detected to apply for automatic cooking of food.

5 Industrial Applicability

10

As aforementioned, the absolute humidity sensor according to the present invention has the following advantages.

The polyimide thin film, which absorbs the humidity greater than a ceramic based humidity sensing material, is used as a humidity sensing material, and a silicon wafer is used as a substrate. Thus, an absolute humidity sensor susceptible to humidity can be fabricated and at the same time the sensor can be integrated using a silicon process. This simplifies the package process and facilitates mass production of the sensor.

The foregoing embodiments are merely exemplary and are not to be construed as limiting the present invention. The present teachings can be readily applied to other types of apparatuses. The description of the present invention is intended to be illustrative, and not to limit the scope of the claims. Many alternatives, modifications, and variations will be apparent to those skilled in the art.

What is claimed is:

- 1. An absolute humidity sensor comprising:
- a silicon substrate;
- a humidity sensing element formed on a substrate, for detecting humidity exposed to the air, having a variable resistance value depending on the amount of the detected humidity;
 - a temperature compensating element formed on the semiconductor, for compensating for the resistance value of the humidity sensing element; and
- a passivation film covered on the temperature compensating element, for shielding the humidity exposed to the air so as not to vary the resistance value of the temperature compensating element.
- 2. The absolute humidity sensor of claim 1, wherein the humidity sensing element and the temperature compensating element include:
 - an insulating film formed on the substrate;
 - a humidity sensing film formed on the insulating film, for absorbing the humidity; and
- an electrode formed below the humidity sensing film or over/below the humidity sensing film.
 - 3. The absolute humidity sensor of claim 2, wherein the insulating film is formed of any one of SiO_2 , Si_3N_4 , and SiO_xN_y .

4. The absolute humidity sensor of claim 2, wherein the humidity sensing film is formed of polyimide.

5. The absolute humidity sensor of claim 2, wherein the electrode has a comb shape.

5

- 6. The absolute humidity sensor of claim 2, wherein the electrode formed only over the humidity sensing film has a comb shape.
- 7. The absolute humidity sensor of claim 1, wherein the passivation film is formed of any one of SiO_2 , Si_3N_4 , and SiO_xN_y .
- 8. The absolute humidity sensor of claim 1, further comprising:

 a printed circuit board joined with a lower portion of the silicon substrate;
 - a wire for electrically connecting electrodes of the humidity sensing element and the temperature compensating element with electrodes of the printed circuit board; and
- a metal shield case formed over the printed circuit board to cover an entire surface of the printed circuit board including the humidity sensing element and the temperature compensating element.
- 9. The absolute humidity sensor of claim 8, wherein the metal shield case has a hole for propagation of external humidity.